

Service levels colour groups:

Back to Basic	2
Lights of Nature	2
Sweet Romance	3
Menpower	3
Mixed Cultures	3
Black & White	3
Fresh & Fruity	3

Technical specifications:

Solar Transmission	6%
Solar Reflection aluminium	64%
Light Transmission	5%
Light Reflection aluminium	63%
UV Transmission	3%
Openness Factor	1,2%
Colour rendering index	99%
LT-value *	4%
g-value *	18%
U-value (W/m ² K) *	0,7
Weight (g/m ²)	136
Thickness (mm)	0,28
Width (cm)	220 (+/- 5 cm)
Yarn composition	Trevira CS

* Properties calculated in combination with Solar control glazing (EN 13363-2, ISO 15099). Measurements according to EN 410.

Flame retardant according to:

Aluminium adhesion
Corrosion resistance
Formaldehyde free
PVC free
Antistatic
Öko-Tex Standard 100

DIN 4102 B1

ISO 6941

BS 5867 Part 2 type B

ISO 2409 class. 0

EN ISO 3231

Yes

Yes

Yes

Yes

Achievable rating according to the European performance rating of shading products, EN 14501:

Glare control

4 (very good)

View through

2 (mild)

g-value

3 (good)

849



Intrinsic flame retardant




Pleated blind



Roller blind



Panel track



*Provides glare control on all façades. Opaque fabrics are perfect in twin products.

* All advices are based on the usage of clear glass and approximately 50% of the façade consists of glass. There should be no mirroring objects in the vicinity.